551,852

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 14 October 2004 (14.10.2004)

PCT

(10) International Publication Number WO 2004/088204 A1

(51) International Patent Classification⁷: F21L 4/08

F21V 23/04,

(21) International Application Number:

PCT/AU2004/000397

(22) International Filing Date: 29 March 2004 (29.03.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2003901553

3 April 2003 (03.04.2003) AU


- (71) Applicant (for all designated States except US): EV-EREADY BATTERY COMPANY, INC. [US/US]; 533 Maryville University Drive, St. Louis, MO 63164 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): DALTON, David, Richard [AU/AU]; 19 Stonecrop Road, Turramurra, New South Wales 2074 (AU). KW, Au [CN/CN]; Flat 8, 11/F ManHor House, Chun Man Court, 66 Chung Hau Street, Ho Man Tin, Kowloon, Hong Kong (CN). KOTSIS, Angelo [AU/AU]; 34 Beauchamp Street, Marrickville, New

South Wales 2204 (AU). **SQUIRES, Michael** [AU/AU]; 285 Morrison Road, Ryde, New South Wales 2112 (AU).

- (74) Agents: BORG, Keith, Joseph et al.; Halford & Co, Level 7, 1 Market Street, Sydney, New South Wales 2000 (AU).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: A FLASHLIGHT OR LIGHTING DEVICE



(57) Abstract: A flashlight (10) including: a housing (12) with a light source (104), a power source (142), and an aperture (126) through the housing (12) that is closed by a resilient cover (112). The resilient cover (112) extends over a switch assembly (18) and provides a waterproof seal for the housing (12). An indicator means (146), when illuminated, is visible through the resilient cover (112). A waterproof flashlight (10) having an electric contact (154) extending through a contact aperture (38) formed in the housing (12) with resilient sealing means (164) between to establish a water tight seal. A securement means (158) to place the resilient means (164) under compression. When not in use, the flashlight (10) may be stowed on a base (40) for recharging through the electrical contact (154).



WO 2004/088204 A1



Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.